

VIP™ Driver

ABOUT THIS UNIT

VIP™ Driver is at the heart of the VIP™ video display system, acting as the interface between any DVI or HDMI video source and all MVP™ or PVP™ video panels via the LED Studio software (provided free). Rack-mountable, it has two signal outputs, which connect through etherCON® to any configuration of the MVP™ or PVP™ panels. The system features a total output of 1280x1024. VIP™ Driver allows media playback, configuration, addressing and remote power control of the MVP™ and PVP™ panels.

FEATURES

- Required for panel addressing and video conversion to CHAUVET® video panels
- LED Studio software connects directly to the VIP™ Driver via USB for patching and panel configuration
- Accepts either DVI or HDMI input
- 2 etherCON® outputs
- A refresh rate of 60fps ensures flicker-free signal for the video panels
- Capable of up to 1280x1024 resolution, and is scalable to link up to 4 units in a single system



SPECIFICATIONS

- Rackmount: 2U
- Housing Material: Aluminum alloy/steel
- Power Connection: IEC
- Control Connection: USB
- Video Inputs: DVI-I or HDMI
- Video Outputs: etherCON® (2)
- Video Refresh Rate: 60fps
- Max Output Resolution: 1280x1024
- Input Voltage: Auto-ranging 100 - 240VAC 50/60Hz
- Power and Current: 40W, 0.33A @ 120V 60Hz
40W, 0.19A @ 208V 60Hz
40W, 0.17A @ 230V 50Hz
- Weight: 5lbs (2.27kg)
- Size: 19 x 10 x 1.7in
(483 x 254 x 44mm)
- IP Rating: IP20
- Approvals: CE, ROHS, FCC