

VIP™ Signal Distributor

ABOUT THIS UNIT

VIP™ Signal Distributor (required for systems over 24 panels) splits and amplifies the signal from the VIP™ Driver to the panels and is capable of 4-way, dual-channel splitting or 8-way, single-channel splitting.



FEATURES

- Distributes and amplifies the output from the VIP™ Driver for up to 192 panels
- The VIP™ Signal Distributor is required for systems of 25 or more video panels
- Serves as a 2-channels, 4-way or 1-channel, 8-way device
- You may link multiple units together for greater quantities
- Required for signal cable runs over 100m

SPECIFICATIONS

- Rackmount: 2U
- Housing Material: Aluminum alloy/steel
- Power Connection: IEC
- Video Inputs: etherCON® (2)
- Video Outputs: etherCON® (8)
- Video Refresh Rate: 60fps
- Input Voltage: Auto-ranging 100-240VAC 50/60Hz
- Power and Current: 40W, 0.33A @ 120V 60Hz
40W, 0.19A @ 208V 60Hz
40W, 0.17A @ 230V 50Hz
- Weight: 5lbs (2.27kg)
- Size: 19 x 10 x 1.7in
(483 x 254 x 44mm)
- IP Rating: IP20
- Approvals: CE, ROHS, FCC